



CBL-SMNM+
(SMA-N Male)



CBL-SMSM+
(SMA Male)



CBL-NMNM+
(N Male)

Outline Dimensions (inch/mm)

Case Style	A	B	C	D	E	T	WT. Grams
GM1006-2	24.0	.42	.312	.42	.312	.75	57
	609.60	10.67	7.92	10.67	7.92	19.05	
GM1006-3	36.0	.42	.312	.42	.312	1.08	75
	914.40	10.67	7.92	10.67	7.92	27.43	
GM1006-4	48.0	.42	.312	.42	.312	1.44	94
	1219.20	10.67	7.92	10.67	7.92	36.58	
GM1006-6	72.0	.42	.312	.42	.312	2.16	131
	1828.80	10.67	7.92	10.67	7.92	54.86	
GM1006-11	144.0	.42	.312	.42	.312	4.32	242
	3657.60	10.67	7.92	10.67	7.92	109.73	
GM1006-7	18.0	.42	.312	.42	.312	.75	47
	457.20	10.67	7.92	10.67	7.92	18.29	
GM1105-2	24.0	.42	.312	.88	.812	.75	96
	609.60	10.67	7.92	22.35	20.62	19.05	
GM1105-3	36.0	.42	.312	.88	.812	1.08	114
	914.40	10.67	7.92	22.35	20.62	27.43	
GM1105-4	48.0	.42	.312	.88	.812	1.44	133
	1219.20	10.67	7.92	22.35	20.62	36.58	
GM1105-6	72.0	.42	.312	.88	.812	2.16	170
	1828.50	10.67	7.92	22.35	20.62	54.86	
GM1105-7	180	.42	.312	.88	.812	5.40	336
	4572	10.67	7.92	22.35	20.62	137.16	
GM1106-2	24.0	.88	.812	.88	.812	.75	135
	609.60	22.35	20.62	22.35	20.62	19.05	
GM1106-3	36.0	.88	.812	.88	.812	1.08	153
	914.40	22.35	20.62	22.35	20.62	27.43	
GM1106-6	72.0	.88	.812	.88	.812	2.16	209
	1828.50	22.35	20.62	22.35	20.62	54.86	
GM1106-7	180.0	.88	.812	.88	.812	5.40	375
	4572	22.35	20.62	22.35	20.62	137.16	
GM1106-8	240.0	.88	.812	.88	.812	7.20	468
	6096	22.35	20.62	22.35	20.62	182.88	
GM1106-9	300.0	.88	.812	.88	.812	9.00	560
	7620	22.35	20.62	22.35	20.62	228.60	
GM1132-2	24.0	.51	-	.88	.812	.75	101
	609.60	12.95	-	22.35	20.62	19.05	
GM1132-3	36.0	.51	-	.88	.812	1.08	119
	914.40	12.95	-	22.35	20.62	27.43	
GM1132-6	72.0	.51	-	.88	.812	2.16	175
	1828.80	12.95	-	22.35	20.62	54.86	
GM1133-3	36.0	.51	-	.42	.312	1.08	80
	914.40	12.95	-	10.67	7.92	27.43	

Typical Performance Curves Over Temperature

