

Saw Devices

VCO

P/N (MHz)	Center Frequency	Supply Voltage (V) (MHz/V)	Control voltage Sensitivity (mm)	Package (LxWxH)	Application
TV0105A	748	2.84	12	8.2x6.0x1.6	WLAN
TV0114B	915	2.85	25	8.2x6.0x1.6	Transceiver
TV0119A	1000	3	24	8.2x6.0x1.6	
TV0123A	1600	3	145	8.2x6.0x1.6	
TV0104A	2074	2.84	80	8.2x6.0x1.6	WLAN

VC-TXCO

P/N	Center Frequency (MHz)	Supply Voltage (V)	Fo/Tc Tc Range (d B Max)	Package (LxWxH mm)
TX0173A	12	3	0.5ppm/3ppm/-40C~+85C	5.0x3.2x1.2
TX0156A	16.367667	3.3	1ppm/2.5ppm/-40C~+85C	5.0x3.2x1.2
TX0159A	19.44	3	2ppm/2.5ppm/-30C~+75C	5.0x3.2x1.4
TX0158A	35.328	3.3	50ppm/50ppm/-10C~+70C	7.0x5.0x1.8
TX0225A	40	2.8	1ppm/2ppm/-30C~+85C	3.2x2.5x1.3
TX0147A	54	3.3	25ppm/0C~+70C	7.2x5.2x1.8
TX0171A	100	3.3	5ppm/25ppm/0C~+70C	7.2x5.2x1.8
TX0172A	125	3.3	5ppm/25ppm/0C~+70C	7.2x5.2x1.8
TX0139A	155.52	3.3	50ppm/-5C~+85C	7.2x5.2x1.8
TX0141A	622.08	3.3	50ppm/-5C~+85C	7.2x5.2x1.8

