

# New Product Announcement!

Xtra Long Life 100 million cycles

## USB RF SPDT Switch

USB-1SPDT-A18XL

USB RF SPDT Switch DC-18GHz

### The Big Deal

- Capable of 100 million cycles
- Wide frequency range (DC to 18GHz)
- SPDT electromechanical, absorptive, RF switch (Isolation 85 dB typ.)
- Includes control software with an API DLL com object
- USB 2.0 Device, USB 1.1 compatible
- USB HID device compatible with 32/64 Bit operating systems



Case Style: LM1580

Installation CD with Software included

Pricing: **\$279.00** (QTY 1-4)

### Product Overview

Mini Circuits' USB-1SPDT-A18XL is a general purpose USB controlled RF switch box containing an electro-mechanical SPDT, absorptive, failsafe RF switch constructed in break-before-make configuration and powered by +24V<sub>DC</sub> with a switching time of 25 mSec typical. The RF switch can be set remotely using the supplied GUI program, or programmed by the user using the included API DLL com object. The RF switch operates over a wide frequency band from DC to 18GHz has low insertion loss (0.2 dB typical) and high isolation (85dB typical) making it perfectly suitable for a wide variety of RF applications.

The USB-1SPDT-A18XL is constructed in a plastic case (size of 4.26" X 6.08" X 2.25") case with 3 SMA(F) connectors(IN, J1, J2), a 2.1mm DC socket, and a USB B port. The model is supplied along with a CD containing a graphical user interface program featuring an API DLL com object. Also included is a 2.7ft. USB cable, and a power adapter suitable for both US and EU systems. Longer USB cables are available as additional options.

### Key Features

Feature	Advantages
USB HID (Human Interface Device)	Plug-and-Play (no need to install a driver for the device).
RF SPDT Electromechanical switch	Wideband (DC to 18GHz) with low insertion loss (0.2 dB typ.), very high isolation (85dB typ.), and high power rating (10W cold switching)
24V <sub>DC</sub> Operating voltage	The USB-1SPDT-A18XL requires 24V/500mA to power the RF switches, supplied from the included power adapter.
32/64 Bit operating systems	Compatible with Windows and Linux operating systems using 32 and 64 bit architecture.
Software CD, USB cable and 24V <sub>DC</sub> Power adapter included	A CD containing a programming manual for Linux and windows operating systems (32 and 64 bit systems) and a Windows GUI program containing an API DLL com object is included with the USB-1SPDT-A18XL. A 2.7ft. USB cable and a power adapter with both US and EU connectors are also included.



For detailed performance specs & shopping online see web site

P.O. Box 350166, Brooklyn, New York 11235-0003 (718) 934-4500 Fax (718) 332-4661 **The Design Engineers Search Engine** Provides ACTUAL Data Instantly at [minicircuits.com](http://minicircuits.com)

IF/RF MICROWAVE COMPONENTS

**Notes:** 1. Performance and quality attributes and conditions not expressly stated in this specification sheet are intended to be excluded and do not form a part of this specification sheet. 2. Electrical specifications and performance data contained herein are based on Mini-Circuit's applicable established test performance criteria and measurement instructions. 3. The parts covered by this specification sheet are subject to Mini-Circuits standard limited warranty and terms and conditions (collectively, "Standard Terms"); Purchasers of this part are entitled to the rights and benefits contained therein. For a full statement of the Standard Terms and the exclusive rights and remedies thereunder, please visit Mini-Circuits' website at [www.minicircuits.com/MCLStore/terms.jsp](http://www.minicircuits.com/MCLStore/terms.jsp).